





The Labcold Breast Milk refrigerator has been specifically designed to store human milk in optimum conditions. With three adjustable shelves and an interior fan for even temperature distribution, this fridge is fitted with a lock for extra security.



The flat touch screen controller displays the internal temperature of the fridge, but it also shows minimum and maximum temperatures which can be displayed at the touch of a button. It also alarms if the internal temperature drops below 0°C or rises above 5°C. The Breast Milk fridge is also fitted with a door open alarm and, if batteries are fitted, a mains failure alarm.

There is also a second temperature probe which can be placed where ever you see fit. The controller will also display the temperature of that probe and alarm when it detects high or low temperatures plus record min/max readings.



The IntelliCold<sup>®</sup> controller automatically stores temperature data for both probes and refrigerator performance. A specifically encoded Micro SD card is available as an optional extra for data transfer so these records can be stored to your PC. Why not ask for details when you place your order?



## RLBM0519 Breast Milk Refrigerator

Part Number	RLBM0519
Capacity (Litres)	150
Style	Under Counter
Exterior Dimensions (HxWxD)	835 x 600 x 600mm
Interior Dimensions (HxWxD)	690 x 480 x 410mm
Temperature Range	0°C to 5°C
<b>Operating Temperature</b>	+3°C
Interior Construction	Powder Coated Steel
Exterior Construction	Powder Coated Steel
Shelves	3
Adjustable Feet	$\checkmark$
Automatic Temperature & Fridge Operation Data Recording	$\checkmark$
Door Style	Solid
Door Hinging	Right (can be reversed at time of manufacture)
Door Lock	$\checkmark$
Self Closing Door	$\checkmark$
Digital Temperature Control	$\checkmark$
Digital Temperature Display	√
Internal Light	$\checkmark$
High/Low Temperature Alarm	$\checkmark$
Minimum/Maximum Temperature Recording	$\checkmark$
Door Open Alarm	$\checkmark$
Mains Failure Alarm	$\checkmark$
Alarm Battery Back-Up	$\checkmark$
Off cycle auto defrost	$\checkmark$
Second Temperature Probe	$\checkmark$
Fan Assisted Cooling	$\checkmark$
Remote Alarm Contacts	$\checkmark$
Access Port	$\checkmark$
Low GWP Refrigerant	$\checkmark$

