

## CHROMATOGRAPHY 700 ECT-F



### Characteristics

Temperature Range	+2/+15°C
Capacity	620 lt (21,91 cu ft) <i>Gross capacity 620 lt (21,91 cu ft)</i>
External Dimensions (W x D x H)	cm 75 x 84 x 210 <i>Internal Dimensions (W x D x H) cm 60 x 68,6 x 150,5; Weight kg 135</i>
Structure and Insulation	stainless steel 18/10 AISI 304 inside and sanitized pre-coated steel white colour- outside; insulation polyurethane thickness 75 mm
Feet	n.4 adjustable feet
Door	Nr 1 glass door with triple glass panels
Light	Led type with adjustable brightness
Internal equipment	n.1 stainless steel sliding shelf
Controller	ECT-F  <i>ECT-F CONTROL with LCD Display with no.4 soft touch pads, with a 0,1 °C resolution. Customizable menu, available in 5 languages. Acoustic and visual signals for:</i>  <ul style="list-style-type: none"> <li>• Open door</li> <li>• High Temperature</li> <li>• Low temperature</li> <li>• Power failure (when the energy returns, only in event of High Temperature)</li> <li>• Dirty Condenser The last 12 events are always available from the display. Clear and precise information of the status of the machine are indicated on the display, as well as all the failures. A password, if enabled, identifies two distinct levels of access to the controller (User and Service), and protects the modification of functional parameters, such as switch on, switch off and set-point of the equipment. The display can be customized, enabling you instant verification of all the main settings for a quick resolution of any problems (Doctor View). Special functions Stop-On-Door, Second Cooling and Advanced Defrosting allow the complete management of the refrigeration cycle, reducing temperature peaks and consumption.</li> </ul>
Alarms	Acoustic and Visual for temperature deviations and failures
Data and Event recording	last 12 events available from display
Cable port mm.35 with cap	n.1
Internal socket (nr.2 with ON/OFF)	n.1
Refrigeration Type	Forced-air, ventilated
Defrost	Automatic with automatic evaporation of the condensate water

### Technical data

Technical Data	<ul style="list-style-type: none"> <li>• Refrigerant gas type: R134A CFC free</li> <li>• Mains Voltage 230V/1/50Hz</li> <li>• Power consumption 24H: 1,6 kW/24H</li> <li>• Instant power consumption: 0,29 kW (1,63 A)</li> <li>• Heat emission: 598W</li> <li>• Noise level &lt; 50 dB</li> <li>• Ambient Temperature: +16/+38 °C; humidity 60%</li> <li>• Connector: Schuko</li> </ul>
In accordance with	2006/42/CE, 2014/30/CE, 2014/35/CE, 2011/65/CE (RHoS), 2012/19/CE (RAEE) and following modifications
Package	Strong Cardboard on wooden pallet

## Accessories

---

Key Lock

ECT-F PLUS CONTROLLER

- - Backup batteries for power alarm up to 48Hrs (24 for 2T)
- Memory of Min and Max temperature reached, resettable by user
- High temperature alarm due to power failure alarm
- Temperature displayed during power failure
- Free contact on the electronic board
- Additional output relays

Blind Door

Additional Shelf

Wire basket in stainless steel H mm 148

Sliding wire stainless steel drawer H mm 62

Dry Contact

Castors (2 with with brakes)

Internal Socket

Internal Sockets (n.2 with On/OFF)

Cable port mm 35 with cap

Cable port mm 15

Humidity Sensor

PT100 probe (free contacts)

Voltage stabilizer

60 Hz Frequency

115 V

Wooden crate Package

---