



## LogTag® LTI-HID Desktop USB Interface Cradle

The new LTI-HID desktop USB interface cradle replaces the current LTI/USB interface.

The LTI-HID uses interface drivers that are built into all currently supported Windows OS versions, so there is no longer any need to install proprietary drivers.

The LTI-HID is compatible with all standard LogTag® recording products having 3 silver contact pins in the lower rear case.

The LTI-HID uses the proven and reliable spring contact arrangement taken from the LTI/USB. The LTI-HID incorporates a micro USB socket for connection to a computer.

Two indicators at the top (red & green), identify what actions the interface is currently performing:

- When a Logger is inserted, the green indicator turns off, the red indicator turns on and remains on while Logger and software exchange information, (E.g. during data download or configuring the Logger). When the data exchange is complete, the green indicator flashes to show that the recorder can now be removed, or further data exchange can be initiated (E.g. starting the configuration process after an automatic download).
- When the Logger is removed, the green indicator turns on again and signals that the interface is ready to receive the next Logger.



<b>Product Model</b>	LTI-HID
<b>Operating Temperature Range</b>	-20°C to +60°C
<b>Storage Temperature Range</b>	-40°C to +70°C
<b>USB Standard</b>	2.0
<b>Environmental</b>	IP50 (Rated for indoor use only)
<b>Software Compatibility</b>	LTA 2.9r2, LTA 3.0r8, LTX 1.1r1 LogTag Online
<b>Indicators</b>	Green 'Activity' LED. Red 'Busy/Error' LED
<b>Power Source</b>	Powered from computer
<b>Size</b>	45mm(h) x 85mm(W) x 71mm(D), excluding cable
<b>Weight</b>	74g, excluding cable
<b>Case Material</b>	Polycarbonate, ABS
<b>Connection</b>	USB Micro
<b>Certifications</b>	FCC, CE & RoHS Compliant
<b>Accessories</b>	1.0m USB Cable