

BioPlus 930



Biostorage you can depend on



BioPlus 930

The **BioPlus 930** range is designed for the storage of the most delicate biomaterials, in situations where even tiny fluctuations in conditions inside the storage cabinet can have a serious effect on the contents.

BioPlus ER cabinets also enable you to reduce internal relative humidity, thus cutting down on any likelihood of undesirable contaminants getting near delicate biomaterials.

In terms of performance, these units are designed to provide the very best results even under exceptional conditions. The BioPlus utilises environmentally responsible HFC-free foam propellants and is available with HFC-free refrigerants.



The BioPlus 930 is available as a refrigerator or freezer in either white or stainless steel finish. All BioPlus models come with self-closing door. Glass door is available for refrigerator.



II 3G Ex nA nC nL IIB T2 Gc

Biostorage
you can
depend on

Version 03. Valid from 19.10.20



BioPlus 930



Biostorage you can depend on

Top panel with BioLine control unit

The MPC unit is specially developed for users of BioLine storage cabinets. Among its many features are acoustic temperature and door alarms, and a voltage-free contact (NO/NC) for remote alarms. The display can be easily locked.




Access port

24.5 mm port for ease of access, e.g. sensors for external temperature surveillance.



E-sensor

Extra sensor for providing a temperature reference within the storage compartment.



Shelves and drawers

A wide range of versatile interior fittings and layouts is available. The operating specifications and the interior layout can both be customised.




Stainless steel interior

The internal sides and bottom as well as shelf and drawer brackets and support rails are made of stainless steel.

ATEX

All BioPlus models comply with ATEX Cat.3 Zone 2 requirements, both internal and externally, allowing for placement in locations where explosive gas atmospheres may be present.



AIR DISTRIBUTION

The unique Gram BioLine air distribution system makes sure the temperature inside the cabinet remains stable at all times, while using the minimum amount of energy.

| Technical specifications | BioPlus ER930 | BioPlus RF930 |
|----------------------------------|--|-------------------------------|
| Temperature range | +20/-2 °C | -5/-25 °C |
| Ambient temperature range | Solid door +10/+43 °C; Glass door +10/+38°C | |
| Control Unit | Gram Control Unit with voltage-free contact, E-sensor, acoustic and visual door and temperature alarms that can be programmed individually, alarm recording and offset function. | |
| Material interior | Stainless steel | |
| Material exterior | White lacquered steel or stainless steel | |
| Dimensions mm (W x D x H) | 780 x 1045 x 2025/2275 | |
| Gross volume | 930 litres/32.8 cubic feet | |
| Net volume | 702 litres/30.0 cubic feet | |
| Net weight | Unpacked net weight without optional fittings: 165 kg | |
| Modules for shelves and drawers | Shelves 27 | |
| Insulation | 60 mm polyurethane with HFC-free cyclopentane propellant | |
| K-Value | Glass door 0.4563 W/m²K | Solid door 0.3137 W/m²K |
| Refrigerant | R290 / R134a | R290 / R404A |
| Co ₂ e | R134a: 572 | R404A: 1177 |
| Refrigeration capacity at -10 °C | R290 389 watt; R134a 314 watt | - |
| Refrigeration capacity at -25 °C | - | R290 627 watt; R404A 487 watt |
| Base | Legs* | |
| Energy consumption | 2.10 kWh/24h | 6,12 kWh/24h |
| Sound level | 48,5 db(A) | 49,5 db(A) |
| Connection | 230 V, 50 Hz | |
| Air system | Gram BioLine ventilated air distribution system | |
| Defrost system | Automatic smart defrost with re-evaporation of defrost water | |

* The cabinets can also be delivered with castors or for mounting on a plinth at no extra charge