



## BIOMEDICAL REFRIGERATOR + 1° / + 10° C - GLASS DOOR

| MODELS  | VOLUME (Lt) | INNER DIMENSIONS (mm) |     |      | OUTER DIMENSIONS (mm) |     |      |
|---------|-------------|-----------------------|-----|------|-----------------------|-----|------|
|         |             | W                     | D   | H    | W                     | D   | H    |
| BMR628G | 628 L       | 603                   | 694 | 1500 | 740                   | 830 | 2037 |

|                            |   |
|----------------------------|---|
| <b>CAPACITY</b>            | 628 L   |
| <b>TEMPERATURE RANGE</b>   | + 1° C / + 10° C  |
| <b>AMBIENT TEMPERATURE</b> | MAX.+ 32° C   |
| <b>NO. OF COMPRESSOR</b>   | 1   |
| <b>POWER</b>               | 230V / 50 HZ  |
| <b>ALARMS</b>              | VISUAL / ACOUSTIC ALARM • OPEN DOOR ALARM • ALARM DISPLAY AS TEXT - NOT CODES • POWER FAILURE ALARM • ADJUSTABLE HIGH / LOW TEMPERATURE ALARM • APPROX. 48 HRS. OF BATTERY BACKUP FOR ALARMS AND TEMPERATURE DISPLAY IN THE EVENT OF POWER CUT • TRACK OF ALARMS TO BE NOTED AUTOMATICALLY • PROBE FAILURE ALARM • CONTACT REMOTE ALARM |
| <b>BACK UP</b>             | 48 HOURS BATTERY BACKUP FOR LOGGING ALARMS & TEMPERATURE DISPLAY IN CASE OF POWER FAILURE   |
| <b>ISOLATION</b>           | 70 MM   |
| <b>WEIGHT</b>              | 125 KG  |
| <b>SHELVES</b>             | 3   |
| <b>MAX. SHELF LOAD</b>     | 30 KG   |
| <b>DISPLAY</b>             | TOUCH SCREEN • INTERGRATED DATALOGGER • RS485 INTERFACE • USB UP/ DOWN LOAD • MEMORY FOR OVER 15 YEARS OF DATA • DATE & TIME • DIFFERENT LANGUAGES • PASSWORD PROTECTED • TEMPERATURE GRAPH   |
| <b>CASTORS LOCKABLE</b>    | 4 CASTORS - 2 LOCKABLE  |
| <b>DEFROST</b>             | AUTOMATIC   |
| <b>LIGHTING</b>            | YES   |
| <b>KEY LOCK</b>            | YES   |
| <b>NO. OF DOORS</b>        | 1 GLASS DOOR  |
| <b>REFRIGERANT</b>         | R290  |
| <b>CHAMBER MATERIAL</b>    | STAINLESS STEEL   |
| <b>EXTERIOR MATERIAL</b>   | POWDER COATED GALVANIZED STEEL  |
| <b>DOCUMENTATION</b>       | IQ • OQ • PQ • PQ TEST  |

We reserve the right to change specifications without notice. Subject to confirmation, availability and errors.