

BIOMEDICAL REFRIGERATOR + 1° / + 10° C - GLASS DOOR

MODELS	VOLUME (Lt)	INNER DIMENSIONS (mm)			OUTER DIMENSIONS (mm)		
		W	D	H	W	D	H
BMR1398G	1398 L	1343	694	1500	1480	830	2037



CAPACITY	1398 L
TEMPERATURE RANGE	+ 1° C / + 10° C
AMBIENT TEMPERATURE	MAX. + 32° C
NO. OF COMPRESSOR	1
POWER	230V / 50 HZ
ALARMS	VISUAL / ACOUSTIC ALARM • OPEN DOOR ALARM • ALARM DISPLAY AS TEXT - NOT CODES • POWER FAILURE ALARM • ADJUSTABLE HIGH / LOW TEMPERATURE ALARM • APPROX. 48 HRS. OF BATTERY BACKUP FOR ALARMS AND TEMPERATURE DISPLAY IN THE EVENT OF POWER CUT • TRACK OF ALARMS TO BE NOTED AUTOMATICALLY • PROBE FAILURE ALARM • CONTACT REMOTE ALARM
BACK UP	48 HOURS BATTERY BACKUP FOR LOGGING ALARMS & TEMPERATURE DISPLAY IN CASE OF POWER FAILURE
ISOLATION	70 MM
WEIGHT	180 KG
SHELVES	6
MAX. SHELF LOAD	30 KG
DISPLAY	TOUCH SCREEN • INTERGRATED DATALOGGER • RS485 INTERFACE • USB UP/ DOWN LOAD • MEMORY FOR OVER 15 YEARS OF DATA • DATE & TIME • DIFFERENT LANGUAGES • PASSWORD PROTECTED • TEMPERATURE GRAPH
CASTORS LOCKABLE	5 CASTORS - 2 LOCKABLE
DEFROST	AUTOMATIC
LIGHTING	YES
KEY LOCK	YES
NO. OF DOORS	2 GLASS DOORS
REFRIGERANT	R290
CHAMBER MATERIAL	STAINLESS STEEL
EXTERIOR MATERIAL	POWDER COATED GALVANIZED STEEL
DOCUMENTATION	IQ • OQ • PQ • PQ TEST

We reserve the right to change specifications without notice. Subject to confirmation, availability and errors.