

## BIOMEDICAL FREEZER -30° C

MODELS	VOLUME (Lt)	INNER DIMENSIONS (mm)			OUTER DIMENSIONS (mm)		
		W	D	H	W	D	H
BMF1398	1398 L	1343	694	1500	1480	830	2037



<b>CAPACITY</b>	1398 L
<b>TEMPERATURE RANGE</b>	-30° C / -10° C
<b>AMBIENT TEMPERATURE</b>	MAX.+ 32° C
<b>NO. OF COMPRESSOR</b>	1
<b>POWER</b>	230V / 50 HZ
<b>ALARMS</b>	VISUAL / ACOUSTIC ALARM • OPEN DOOR ALARM • ALARM DISPLAY AS TEXT - NOT CODES • POWER FAILURE ALARM • ADJUSTABLE HIGH / LOW TEMPERATURE ALARM • APPROX. 48 HRS. OF BATTERY BACKUP FOR ALARMS AND TEMPERATURE DISPLAY IN THE EVENT OF POWER CUT • TRACK OF ALARMS TO BE NOTED AUTOMATICALLY • PROBE FAILURE ALARM • CONTACT REMOTE ALARM
<b>BACK UP</b>	48 HOURS BATTERY BACKUP FOR LOGGING ALARMS & TEMPERATURE DISPLAY IN CASE OF POWER FAILURE
<b>ISOLATION</b>	70 MM
<b>WEIGHT</b>	180 KG
<b>SHELVES</b>	6
<b>MAX. SHELF LOAD</b>	30 KG
<b>DISPLAY</b>	TOUCH SCREEN • INTERGRATED DATALOGGER • RS485 INTERFACE • USB UP/ DOWN LOAD • MEMORY FOR OVER 15 YEARS OF DATA • DATE & TIME • DIFFERENT LANGUAGES • PASSWORD PROTECTED • TEMPERATURE GRAPH
<b>CASTORS LOCKABLE</b>	4 CASTORS - 2 LOCKABLE
<b>DEFROST</b>	AUTOMATIC
<b>KEY LOCK</b>	YES
<b>NO. OF DOORS</b>	2
<b>REFRIGERANT</b>	R290
<b>CHAMBER MATERIAL</b>	STAINLESS STEEL
<b>EXTERIOR MATERIAL</b>	POWDER COATED GALVANIZED STEEL
<b>DOCUMENTATION</b>	IQ • OQ • PQ • PQ TEST

We reserve the right to change specifications without notice. Subject to confirmation, availability and errors.