



- Extensive Range
- 90+ Years of History
- Extended Aftercare Support
- UKAS Laboratory

Intellcold® Pharmacy Fridges

Bench Top RLDF0224DIGLOCK

A next generation pharmacy refrigerator featuring the latest IntelliCold® 24-Range technology, designed for the safe storage of cold chain medicines in line with Public Health England guidance.

An enhanced IntelliCold® touch screen controller delivers accurate timekeeping, intelligent event logging and Bluetooth connectivity for fast access to temperature data via the Labcold Connect Android App. The flat, easy-clean controller locks automatically to prevent accidental changes, while a factory-fitted digital door lock eliminates the risk of lost or shared keys and puts you in control of authorised access. The user code can be changed at any time, with an optional master key available for added reassurance.

Inside, three independent temperature probes provide advanced protection, including a low-temperature safeguard that prevents freezing. A pre-fitted simulated load has been carefully selected to represent the thermal behaviour of commonly stored pharmacy products. This ensures temperature readings reflect true product conditions, providing meaningful alarms when medicines are genuinely at risk; rather than masking excursions with oversized or unrepresentative loads.

Specifications

Product Code	RLDF0224DIGLOCK
Gross Capacity	66 Litres
Style	Bench Top
External Dimensions (mm) HxWxD	735 x 450 x 510
Internal Dimensions (mm) HxWxD	588 x 331 x 226
Temperature Range	2°C to 8°C
Fridge Set Point	5°C

Specifications (cont.)

Internal Material	Moulded Plastic
External Material	Powder Coated Steel
Shelves	3
Net Weight	34 Kg
Door Style	Solid
Lock Type	Digital Lock
Digital Temperature Display	Yes
Digital Temperature Control	Yes
High/Low Temperature Alarm	Yes
Min/Max Temperature Recording	Yes
Integral Temp Data Logging	Yes
Automatic Temperature & Fridge Operation Data	Yes
Number of Temperature Probes	3
Internal Light	Yes
Self Closing Door	Yes
Door Open Alarm	Yes
Mains Failure Alarm	Yes
Alarm Battery Backup	Yes
Auto Defrost	Yes
Fan Assisted Cooling	Yes
Remote Alarm Contacts	Yes
Access Porthole	Yes
Access Porthole Size	12mm
Power Consumption Kwh/24hrs	1.3
Ambient Operating Temperature	16°C to 32°C

Features

- Fitted with the IntelliCold® touch screen controller
 - 24/7 automatic temperature logging which is accessible via Bluetooth App
 - Fan assisted cooling
 - T3 Sensor & Low-Temperature Cut
 - Controller and alarm battery back up
 - Minimum/maximum temperature recording and display
 - Auto defrost
 - Self-closing door
 - Remote alarm contacts
 - Compliant with all leading professional guidelines
 - Event based logging
 - Digital lock
 - Realistic pre-fitted simulated Load
 - High/Low temperature alarm
 - Door open and power failure alarm
 - Access port for additional monitoring equipment
 - Internal light
 - Brackets for wall mounting
-

Accessories



Master Key
LABLOCK3KEYS