





## Color: **Inox** Panel: **LITE**

- LED backlit control panel
- Temperature display resolution 0,1°C
- Audible and visual alarms
- Dry contact for alarms signal remoting

## **TECHNICAL FEATURES**

Product Code	AKG252L
Temperature	0°C / +15°C   -5°C / -20°C
Refrigeration Type	Forced air
Condensate Evaporation	Automatic
Refrigerant Gas	R290

## LCRF 625 S LITE



TECHNICAL FEATURES		
Climatic Class	+16°C / +32°C (N)	
External Dimensions (W x D x H mm)	750 x 850 x 2080	

ELECTRICAL DATA	
Power Supply (V/ph/Hz)	220-230/1/50
Power Plug	Type F

STRUCTURAL FEATURES		
Structure	Upright	
External Material	Stainless steel 18/10 AISI 304	
Internal Material	Stainless steel 18/10 AISI 304	
Insulation Thickness (mm)	75	
Insulated Door	Yes	
Automatic Door Closure	Yes	
Shelves Number	2/2	
Shelf Material	Wire steel with white colour plastic coating	
Shelves Dimensions (W x D mm)	530 x 650	
Shelf Adjustment Step Range (mm)	89	
Maximum Shelf Quantity	-	
Drawers with extractable slides	Optional	
Drawer Adjustment Step Range (mm)	89	

CONTROL PANEL		
Display Type	LED	
Access Password	No	
Probe Type	Nr. 2 NTC	

## LCRF 625 S LITE



CONTROL PANEL		
Alarm Signaling	Acoustic and visual	
Alarm Indications	Codes	
Adjustable High/Low Temperature Alarm	Yes	
Adjustable Door Open Alarm	Yes	
Power Loss Alarm	Yes	
Probe Fault Alarm	Yes	
Acoustic Alarm Silencing Options	Yes	
Calibration	Yes	
Alarm Memory	10	
Dry Contact	Yes (NC)	