

Data sheet

- (+48) 32 453 91 70
- info@pol-eko.com.pl
- www.pol-eko.com.pl

POL-EKO A.Polok-Kowalska sp.k.
44-300 Wodzisław Śląski
ul. Kokoszycka 172 C

Climatic Chamber KK 115 Smart PRO



The photo above is for reference only, may show additional options not included in standard equipment. The real appearance, particularly color and structure of the material may differ from the ones presented in the photo.

Advantages of the SMART PRO controller:

- large (7"), clear, full colour touch screen
- LAN, USB ports and WiFi for communication and data transfer
- multi-segment time and temperature programs
- overview of data in tabular and graphic form
- visual and sound alarm
- Admin function for management
- password protected log-in
- internal memory for programs and data storage
- event registry with user notifications
- LabDesk software and user manual for direct download



Smart PRO - preview screen






(+48) 32 453 91 70info@pol-eko.com.plwww.pol-eko.com.pl

POL-EKO A.Polok-Kowalska sp.k. 44-300 Wodzisław Śląski ul. Kokoszycka 172 C

TECHNICAL DATA	
air convection	forced
chamber capacity [I]	109
working capacity [I]	109
controller	microprocessor PID
display	7" full colour touch screen
TEMPERATURE AND HUMIDITY	
temperature range [°C]	0+60
temperature resolution every [°C]	0,1
temperature variation at 25°C and 60%rH [+/-°C]*	2,0
temperature protection	class 3.3 to DIN 12880
relative humidity range [%]	3090 (see chart for details)
humidity resolution every [%]	1,0
humidity variation at 25°C and 60% rH [%rH]	5,0



obszar pracy krótkotrwałej (max.24 h) short-term work area (max. 24h)

Wilgotność względna / Relative humidity [%]

CHAMBER	
door type	double (external solid, internal glass) / external glass (option)
interior	
Smart PRO	acid-proof stainless steel to DIN 1.4301
IG Smart PRO	acid-proof stainless steel to DIN 1.4301
housing	
Smart PRO	powder coated sheet
IG Smart PRO	stainless steel linen finish






(+48) 32 453 91 70info@pol-eko.com.plwww.pol-eko.com.pl

POL-EKO A.Polok-Kowalska sp.k. 44-300 Wodzisław Śląski ul. Kokoszycka 172 C

overall dims [mm] /1/	
width A	670
height B	1340
depth C	950
internal dims [mm]	
width D	460
height E	530
depth F	440



shelves (standard max)	2 7
max shelf workload [kg] /2/	10
- reinforced shelf version (PW) [kg] /3/	50
max unit workload [kg]	60
weight [kg]	90

ELECTRICAL PARAMETERS	
voltage**	230V 50-60Hz
nominal power [W]	1350
refrigerant	R1234ze / GWP=7
warranty	24 months
manufacturer	POL-EKO

all the above technical data refer to standard units (without optional accessories)

- * variation (K) calculated for chamber as: K= +/- (T average max. T average min.) / 2
- ** other power supplies on request
- $\ensuremath{\text{1}}$ depth doesn't include 50 mm of power cable
- ${\bf 2}$ on uniformly loaded surface
- 3 reinforced shelf

OPTIONS AND ACCESSORIES



Order number: */A

door with viewing window



Order number: */P INOX

Stainless steel wire shelf INOX




Order number: */PP

Perforated shelf









	Order number: */PW	Reinforced shelf
	Order number: KUW GN*/*	Stainless steel cuvettes
	Order number: */FIT	Phytotron system
	Order number: GNZ	Internal socket
(((((Order number: KK/CP	Low water level sensor
>0<	Order number: BRT/*/L or IQ/OQ/PQ	Calibration and IQ, OQ, PQ qualification
4	Order number: BPP 12	Battery backup for display
ALARM	Order number: PORT ALARM	Dry alarm contact
LAN	Order number: LANK	LAN cable
20mm	Order number: OCZ/20	Non-standard access port 20 mm
30mm	Order number: OCZ/30	Additional access port 30 mm
60mm	Order number: OCZ/60	Non-standard access port 60 mm
100mm	Order number: OCZ/100	Non-standard access port 100 mm
H2O	Order number: KK/Z	Container for deionised water



 $\left(\!\!\left((\,\bullet\,)\right)\!\!\right)$

Order number: KD

Access control