

- (+48) 32 453 91 70
- info@pol-eko.com.pl
- www.pol-eko.com.pl

POL-EKO A.Polok-Kowalska sp.k. 44-300 Wodzisław Śląski ul. Kokoszycka 172 C

> **Drying Oven** SLW 1000 Smart



The photo above is for reference only, may show additional options not included in standard equipment. The real appearance, particularly color and structure of the material may differ from the ones presented in the photo.

Advantages of the SMART controller:

- 4,3", clear, full colour touch screen
- LAN, USB ports for data transfer
- multi-segment time and temperature programs
- visual and sound alarm
- internal memory for programs and data storage
- event registry
- user manual for direct download
- Quick change of program parameters
- Alarm Bar
- operating with gloves on



Smart - preview screen






(+48) 32 453 91 70info@pol-eko.com.plwww.pol-eko.com.pl

POL-EKO A.Polok-Kowalska sp.k. 44-300 Wodzisław Śląski ul. Kokoszycka 172 C

TECHNICAL DATA		
TECHNICAL DATA		
air convection	forced	
chamber capacity [I]	1005	
working capacity [I]	1005	
controller	microprocessor PID	
display	4,3" full colour touch screen	
TEMPERATURE		
temperature range [°C]	5°C above ambient temperature +300°C	
temperature resolution every [°C]	0,1	
temperature fluctuation at 105°C [+/-°C]*	0,6	
temperature variation at 105°C [+/-°C]*	3,0	
temperature protection	class 2.0 to DIN 12880 / class 3.1 (option)	
CHAMBER		
door type	solid / door with viewing window (option)	
interior		
Smart	acid-proof stainless steel to DIN 1.4301	
IG Smart	acid-proof stainless steel to DIN 1.4301	
housing		
Smart	powder coated sheet	
IG Smart	stainless steel linen finish	

overall	dims	[mm] /1/	
---------	------	----------	--

width A	1260
height B	2000
depth C	880
internal dims [mm]	
width D	1040
height E	1610
depth F	600



shelves (standard max)	6 22
- reinforced shelf version (PW) [kg] /3/	100
max unit workload [kg]	300
- reinforced unit version (W) [kg] /4/	300
weight [kg]	307



(+48) 32 453 91 70 info@pol-eko.com.pl www.pol-eko.com.pl POL-EKO A.Polok-Kowalska sp.k. 44-300 Wodzisław Śląski ul. Kokoszycka 172 C

ELECTRICAL PARAMETERS		
voltage**	400V 50-60Hz	
nominal power [W]	5500	
warranty	24 months	
manufacturer	POL-EKO	

all the above technical data refer to standard units (without optional accessories)

st - fluctuation measured in centre of the chamber; in space, variation (K) calculated for chamber as:

K = +/- (T average max. - T average min.) / 2

- ** other power supplies on request
- 1 depth doesn't include 50 mm of power cable
- 2 on uniformly loaded surface
- 3 reinforced shelf
- 4 reinforced version

OPTIONS AND ACCESSORIES

	Order number: */A	door with viewing window
INOX	Order number: */P INOX	Stainless steel wire shelf INOX
	Order number: */PP	Perforated shelf
	Order number: */PW	Reinforced shelf
	Order number: KUW GN*/*	Stainless steel cuvettes
	Order number: OWW/OWW LED	Interior lighting
НЕРА	Order number: HEPA	HEPA Clean Air Filter
LAB DESK	Order numberLabDesk	LabDesk software



>0<

DIN

3.1

Order number: */3.1 Over temperature protection 3.1 class according to DIN 12880



Order number: BPP 12 Battery backup for display

Order number: BRT/*/L or IQ/OQ/PQ

Calibration and IQ, OQ, PQ qualification



(+48) 32 453 91 70info@pol-eko.com.plwww.pol-eko.com.pl

POL-EKO A.Polok-Kowalska sp.k. 44-300 Wodzisław Śląski ul. Kokoszycka 172 C

ALARM D

Order number: PORT ALARM Dry alarm contact

LAN

Order number: LANK LAN cable

20mm

Order number: OCZ/20 Non-standard access port 20 mm

30mm

Order number: OCZ/30 Additional access port 30 mm

60mm

Order number: OCZ/60 Non-standard access port 60 mm

100mm

Order number: OCZ/100 Non-standard access port 100 mm

 $\Big(\!\!\big((\bullet)\!\big)\!\!\Big)$

Order number: KD Access control

