

(+48) 32 453 91 70
info@pol-eko.com.pl

www.pol-eko.com.pl

POL-EKO A.Polok-Kowalska sp.k.
44-300 Wodzisław Śląski
ul. Kokoszycka 172 C

Data sheet VDW Crucial Temperature Solutions

Laboratory Sterilizer SRN 53 Smart




The photo above is for reference only, may show additional options not included in standard equipment. The real appearance, particularly color and structure of the material may differ from the ones presented in the photo.

Advantages of the SMART controller:

- 4,3", clear, full colour touch screen
- LAN, USB ports for data transfer
- multi-segment time and temperature programs
- visual and sound alarm
- internal memory for programs and data storage
- event registry
- user manual for direct download
- Quick change of program parameters
- Alarm Bar
- operating with gloves on










TECHNICAL DATA

air convection	natural
chamber capacity [I]	56
working capacity [I]	56
controller	microprocessor PID
display	4,3" full colour touch screen
TEMPERATURE	
temperature range [°C]	5°C above ambient temperature +250°C
temperature resolution every [°C]	0,1
temperature fluctuation at 105°C [+/-°C]*	0,4
temperature variation at 105°C [+/-°C]*	2,0
temperature protection	class 2.0 to DIN 12880 / class 3.1 (option)
CHAMBER	
door type	solid / door with viewing window (option)
interior	
Smart	acid-proof stainless steel to DIN 1.4301
IG Smart	acid-proof stainless steel to DIN 1.4301
housing	
Smart	powder coated sheet
IG Smart	stainless steel linen finish

overall dims [mm] /1/

590
710
620
400
390
360



shelves (standard max)	2 5
max shelf workload [kg] /2/	25
- reinforced shelf version (PW) [kg] /3/	50
max unit workload [kg]	40
weight [kg]	48





ELECTRICAL PARAMETERS

voltage**	230V 50-60Hz	
nominal power [W]	1700	
warranty	24 months	
manufacturer	POL-EKO	

all the above technical data refer to standard units (without optional accessories)

* - fluctuation measured in centre of the chamber; in space, variation (K) calculated for chamber as:

K= +/- (T average max. - T average min.) / 2

** - other power supplies on request

1 - depth doesn't include 50 mm of power cable

2 - on uniformly loaded surface

3 - reinforced shelf

4 - reinforced version

OPTIONS AND ACCESSORIES

	Order number: */A	door with viewing window
	Order number: */P INOX	Stainless steel wire shelf INOX
	Order number: */PP	Perforated shelf
	Order number: */PW	Reinforced shelf
\bigcirc	Order number: KUW GN*/*	Stainless steel cuvettes
Ø	Order number: QLK*	Castors
	Order number: */S or */S INOX	Table with castors
	Order number: */ST or */S INOX	Base on castors
	Order number: OWW/OWW LED	Interior lighting
HEPA	Order number: HEPA	HEPA Clean Air Filter
LAB DESK	Order numberLabDesk	LabDesk software
	Bank: ING BŚ o/Wodzisław Śląski	Nr rachunku: 90 1050 1403 1000 0022 0879 5498 Nr rej. w BDO 000005609

NIP: 647-216-26-87 | REGON: 276111984 | Sąd Rejonowy w Gliwicach, X Wydział Gospodarczy | KRS 0001009595



ſ

>0<	Order number: BRT/*/L or IQ/OQ/PQ	Calibration and IQ, OQ, PQ qualification
DIN 3.1	Order number: */3.1	Over temperature protection 3.1 class according to DIN 12880
+	Order number: BPP 12	Battery backup for display
	Order number: PORT ALARM	Dry alarm contact
	Order number: LANK	LAN cable
20mm	Order number: OCZ/20	Non-standard access port 20 mm
30mm	Order number: OCZ/30	Additional access port 30 mm
60mm	Order number: OCZ/60	Non-standard access port 60 mm
() 100mm	Order number: OCZ/100	Non-standard access port 100 mm
(((●)))	Order number: KD	Access control

