

(+48) 32 453 91 70

info@pol-eko.com.pl

in

www.pol-eko.com.pl

POL-EKO A.Polok-Kowalska sp.k.
 44-300 Wodzisław Śląski
 ul. Kokoszycka 172 C

SRN 115 Smart





The photo above is for reference only, may show additional options not included in standard equipment. The real appearance, particularly color and structure of the material may differ from the ones presented in the photo.

Advantages of the SMART controller:

- 4,3", clear, full colour touch screen
- LAN, USB ports for data transfer
- multi-segment time and temperature programs
- visual and sound alarm
- internal memory for programs and data storage $% \left(1\right) =\left(1\right) \left(1\right$
- event registry
- user manual for direct download
- Quick change of program parameters
- Alarm Bar
- operating with gloves on



Smart - preview screen






(+48) 32 453 91 70info@pol-eko.com.plwww.pol-eko.com.pl

POL-EKO A.Polok-Kowalska sp.k. 44-300 Wodzisław Śląski ul. Kokoszycka 172 C

air convection	natural		
chamber capacity [I]	112		
working capacity [I]	112		
controller	microprocessor PID		
display	4,3" full colour touch screen		
TEMPERATURE			
temperature range [°C]	5°C above ambient temperature +250°C		
temperature resolution every [°C]	0,1		
temperature fluctuation at 105°C [+/-°C]*	0,4		
temperature variation at 105°C [+/-°C]*	2,2		
temperature protection	class 2.0 to DIN 12880 / class 3.1 (option)	class 2.0 to DIN 12880 / class 3.1 (option)	
CHAMBER			
door type	solid / door with viewing window (option)		
interior			
Smart	acid-proof stainless steel to DIN 1.4301		
IG Smart	acid-proof stainless steel to DIN 1.4301		
housing			
Smart	powder coated sheet		
IG Smart	stainless steel linen finish		

overall	dims	[mm]	/1/

width A	660
height B	850
depth C	710
internal dims [mm]	
width D	460
height E	540
depth F	450



shelves (standard max)	2 7
max shelf workload [kg] /2/	25
- reinforced shelf version (PW) [kg] /3/	50
max unit workload [kg]	60
weight [kg]	65



⟨ +48) 32 453 91 70⋈ info@pol-eko.com.plwww.pol-eko.com.pl

POL-EKO A.Polok-Kowalska sp.k.
 44-300 Wodzisław Śląski
 ul. Kokoszycka 172 C

ELECTRICAL PARAMETERS		
voltage**	230V 50-60Hz	
nominal power [W]	2500	
warranty	24 months	
manufacturer	POL-EKO	

all the above technical data refer to standard units (without optional accessories)

st - fluctuation measured in centre of the chamber; in space, variation (K) calculated for chamber as:

K = +/- (T average max. - T average min.) / 2

- ** other power supplies on request
- 1 depth doesn't include 50 mm of power cable
- 2 on uniformly loaded surface
- 3 reinforced shelf
- 4 reinforced version

OPTIONS AND ACCESSORIES

	Order number: */A	door with viewing window
INOX	Order number: */P INOX	Stainless steel wire shelf INOX
	Order number: */PP	Perforated shelf
	Order number: */PW	Reinforced shelf
	Order number: KUW GN*/*	Stainless steel cuvettes
	Order number: QLK*	Castors
	Order number: */S or */S INOX	Table with castors
	Order number: */ST or */S INOX	Base on castors
	Order number: OWW/OWW LED	Interior lighting
НЕРА	Order number: HEPA	HEPA Clean Air Filter



LAB

DESK

Order numberLabDesk

LabDesk software



(+48) 32 453 91 70info@pol-eko.com.plwww.pol-eko.com.pl

POL-EKO A.Polok-Kowalska sp.k. 44-300 Wodzisław Śląski ul. Kokoszycka 172 C

>0<

Order number: BRT/*/L or IQ/OQ/PQ Calibration and IQ, OQ, PQ qualification

DIN 3.1

Order number: */3.1 Over temperature protection 3.1 class according to DIN 12880

4

Order number: BPP 12 Battery backup for display

ALARM D

Order number: PORT ALARM Dry alarm contact



Order number: LANK LAN cable



Order number: OCZ/20 Non-standard access port 20 mm



Order number: OCZ/30 Additional access port 30 mm



Order number: OCZ/60 Non-standard access port 60 mm



Order number: OCZ/100 Non-standard access port 100 mm



Order number: KD Access control

