

Temperature range

Product technical data sheet

MORTUARY CHAMBER 1 BODY SIDE LOADING

Cod. MCL0001

Characteristics



Disclaimer: Images are purely indicative. The features and the accessories of the products may differ according to model and application.

Capacity	1 body
External Dimensions (WxDxH)	cm 226x86x204 External dimensions without monoblock unit: cm 226x86x166
Structure and Insulation	White coated steel inside and outside; insulation polyurethane thickness 80 mm
Door	n.1 door with side opening
Key Lock	
Light	
Internal equipment	n.1 steel body tray
Controller	Digital electronic thermostat
Alarms	Acoustic and Visual for temperature deviations and failures
Refrigeration Type	Ventilated
Defrost	Automatic with automatic evaporation of the condensate water
	Technical data
Details	 Refrigerant type: R452A, CFC free Mains Voltage 220V/1/50Hz HP 5/8 E Ambient Temperature: +10/+38 °C; Humidity 60% Connector: Schuko
In accordance with	2006/42/CE, 2014/30/CE, 2014/35/CE and following modifications
Package	Chamber to be installed on site, packed in cellophane on pallet,

monoblock in strong cardboard on wooden pallet

+2/+8°C

Accessories

External covering in stainless steel	
DMLP UNIT	External module with DMLP DIGITAL MONITOR Monitor/alarm/recording system with rechargeable battery - Temperatures and alarms recorder on removable Secure Digital (SD Back-Up memory): it can store 5 years data, recording temperature and alarms every minute. The SD card can be connected to any PC: a software (Capture) is included, so that you can download, save and print all data from your PC Battery backup: ensures alarms and recording of temperatures ever in case of power failure. The battery system lasts about 12 hours Dry contact for remote connection + RS485 port
DMLP PRINTER	
Additional body tray	
Hydraulic trolley side loading	