

Temperature range

Product technical data sheet

MORTUARY CHAMBER 3 BODIES SIDE LOADING

Cod. MCL0003

Characteristics



Disclaimer: Images are purely indicative. The features and the accessories of the products may differ according to model and application.

Capacity	3 bodies on 3 levels
External Dimensions (WxDxH)	cm 226x86x262 Internal Dimensions (WxDxH) cm 226x86x226
Structure and Insulation	White coated steel inside and outside; insulation polyurethane thickness 80 mm
Door	n.3 doors with side opening
Key Lock	
Light	
Internal equipment	n.3 steel body trays
Controller	Digital electronic thermostat
Alarms	Acoustic and Visual for temperature deviations and failures
Refrigeration Type	Ventilated
Defrost	Automatic with automatic evaporation of the condensate water
	Technical data
Details	 Refrigerant type: R452A, CFC free Mains Voltage 220V/1/50Hz HP 3/4 Ambient Temperature: +10/+38 °C; Humidity 60% Connector: Schuko
In accordance with	2006/42/CE, 2014/30/CE, 2014/35/CE and following modifications
Package	Chamber to be installed on site, packed in cellophane on pallet, monoblock in strong cardboard on wooden pallet

+2/+8°C

Accessories

xternal module with DMLP DIGITAL MONITOR: Monitor/alarm/recording system with rechargeable battery Temperatures and alarms recorder on removable Secure Digital (SD iack-Up memory): it can store 5 years data, recording temperature and larms every minute. The SD card can be connected to any PC: a software (Capture) is included, so that you can download, save and print all data from your PC Battery backup: ensures alarms and recording of temperatures even in case of power failure. The battery system lasts about 12 hours.
Monitor/alarm/recording system with rechargeable battery Temperatures and alarms recorder on removable Secure Digital (SD tack-Up memory): it can store 5 years data, recording temperature and larms every minute. The SD card can be connected to any PC: a software (Capture) is included, so that you can download, save and print all data from your PC Battery backup: ensures alarms and recording of temperatures even a case of power failure. The battery system lasts about 12 hours.
Dry contact for remote connection + RS485 port