



PURCHASE SPECIFICATIONS: FOR NUAIRE AIREGARD™ ES ENERGY SAVER NU-240E HORIZONTAL LAMINAR FLOW WORK STATION

The intent herein is to provide a concise statement of requirements for a quality Horizontal Laminar Airflow Work Station which may be used to augment your purchase request/order.

The AIREGARD™ ES NU-240E meets the performance requirements of the IEST-RP-CC002.4 and ISO 14644-1.

NuAire sales representatives will be pleased to explain the importance of the performance and control affected by each of the following requirements. The NuAire AIREGARD™ ES NU-240E meets all of the requirements in the following SPECIFICATION.

1. Dimensions Inches (mm)

Overall Dimensions	NU-240-330E	NU-240-430E	NU-240-530E	NU-240-630E
Width (W)	38 (965)	50 (1270)	62 (1575)	74 (1880)
Depth (D)	32 (813)	32 (813)	32 (813)	32 (813)
Height (H)	55 3/8 (1406)	55 3/8 (1406)	55 3/8 (1406)	55 3/8 (1406)
Basestand, 30" W.S.^	81 7/8 (2080)	81 7/8 (2080)	81 7/8 (2080)	81 7/8 (2080)
Basestand, 36" W.S.^	87 7/8 (2232)	87 7/8 (2232)	87 7/8 (2232)	-----
Interior Dimensions				
Width (W)	35 7/8 (911)	47 7/8 (1216)	59 7/8 (1521)	71 7/8 (1826)
Depth (D)	19 5/8 (498)	19 5/8 (498)	19 5/8 (498)	19 5/8 (498)
Height (H)	32 (813)	32 (813)	32 (813)	32 (813)

^Measured using Telescoping Basestand with Leg Levelers

- 2.** Work station shall provide airflow performance as specified.
- a. Work station shall provide ISO 5 quality airflow over the entire work zone for product protection proven by particle test, (e.g. test conducted by NuAire) validated by NuAire.
 - * b. Work station work zone shall be constructed from 16/18 gauge, Type 304 stainless steel.
 - c. Supply HEPA filter 99.99% efficient @ 0.3 microns shall be of full work zone width and height.
 - * d. Supply HEPA filter shall be protected by a perforated metal diffuser.
 - e. Air Velocity from the supply filter shall average 80 to 100 FPM (.41 to .51 m/s) with no single point outside the 20% of average range measured in a horizontal plane defined by 6 inches (102mm) from the diffuser.

*Having all of these features is unique ONLY to NuAire work stations.

- 3.* The Work station shall be ergonomically designed for maximum user comfort and adjustability to meet the requirements of the American Disabilities Act (ADA).
- Work station shall have a large armrest/airfoil radius on the leading edge of the work surface designed for comfort while maximizing product protection performance.
 - Work station shall have a centrally located control center that is easily serviced with quick disconnects.
 - Work station shall have the capability of incorporating a user adjustable basestand or base storage Work station as an option.
 - Work station shall have a large work surface (19-5/8" inch (498mm) depth) by work station width with raised rear spill lip for improved cleaning.
- 4.* The Work station shall have all positive pressure plenums surrounded by a vacuum relative to the room (the AIREGARD™ ES employs the HEPEX™ Zero Leak Airflow System).
5. Electrical power shall be supplied with a 12-foot (2.5m), 3-wire cord with molded plug. Electrical supply should be 230 VAC, 50/60 Hz (Current rating varies per Work station size. Reference electrical requirements) protected with thermal circuit breaker from distribution panel.
6. The Work station shall use a DC ECM Motor with an optimally determined forward-curved fan for each model size/width to maximize both energy efficiency and filter loading capacity.
7. The Work station shall have one internal electrical circuit for the blower and lights. The circuit shall be protected with fuse(s) located in the Control Center on the electronic module.
- 8.* The Work station shall be CE compliant to meet the requirements for electrical/mechanical integrity.
- 9.* Work station shall contain the Aeromax™ control system consisting of electronic modules that will perform the following functions:
- Easy user interface via LED's and function keys
 - Control blower via solid state switch.
 - Control lights via solid state switch.
 - Disable audible alarm switch with ring back function.
 - Control blower DC ECM motor with solid-state DC Motor Controller that provides automatic compensation (constant volume control) for both filter loading and line voltage variances.
 - Monitor and display airflow system performance via PresurFlow™ monitor.
- 10.* Work station shall contain the Aeromax™ control system that provides the following optional functional features (included with Work station, but must be configured during certification):
- Security password protection of Work station use.
 - Work station usage sync functions with blower, fluorescent light.
 - Work station usage auto duration timers, fluorescent light.
11. The Work station shall be easily transportable through a standard 34 inch (864mm) wide door without disassembly.
12. Fluorescent lighting shall be externally mounted and provide a minimum of 90 (968) foot-candles (LUX) on work surface. The ballast is to be electronic containing thermal protection with automatic reset.
13. Work station shall be easily converted to a free-standing console model with the addition of the optional base support stand.
- 14.* Work station work zone shall be all 16/18 gauge stainless steel.
15. Work station exterior shall be constructed of 16/18 gauge powdered coated (light gray) cold rolled steel.
- 16.* Work station shall have a permanent positive pressure plenum with quick release supply filter removal.
- 17.* Motor/blower shall be positioned so as to create an even filter loading, thereby prolonging the life of HEPA filters, automatically handling a 250% minimum increase in filter loading without reducing total air delivery by more than 10%.
- 18.* Work station shall be capable of front filter removal through the work zone without exterior disassembly.

19. The following optional equipment shall be available to support installation and user requirements:

- LED Lighting
- Additional Service Valves for Gas, Air, Vacuum
- Outlets (separate power cord)
- IV Bar with 6 Stainless Steel Hooks
- Base Support Stand (available as telescoping for work surface heights of 30 to 36 inches) (762 to 914mm) with or without Storage Shelves
- Adjustable Control for Support Stand or Storage Work station
- Storage Pull-Out Trays
- GFI Outlets
- Ergotron monitor/keyboard holders
- Polycarbonate side walls
- Laminate (white) work surface

*Having all of these features is unique ONLY to NuAire Work stations.

AIREGARD™ ES Energy Saver Horizontal Laminar Flow Work station
Models NU-240-330E/430E/530E/630E

Catalog Number	Catalog Number			
	NU-240-330E Nominal 3 foot (0.9m)	NU-240-430E Nominal 4 foot (1.2m)	NU-240-530E Nominal 5 foot (1.5m)	NU-240-630E Nominal 6 foot (1.8m)
Performance Specifications	IEST-RP-CC002.4	IEST-RP-CC002.4	IEST-RP-CC002.4	IEST-RP-CC002.4
1. Product Protection	ISO 14644-1	ISO 14644-1	ISO 14644-1	ISO 14644-1
ISO 14644-1	ISO 5	ISO 5	ISO 5	ISO 5
Style of Work station	Bench top/console w/base stand/storage Work station	Bench top/console w/base stand/storage Work station	Bench top/console w/base stand/storage Work station	Bench top/console w/base stand/storage Work station
Work Station Construction	16/18 GA, powder coated steel exterior; 16/18 GA type 304 SST work zone	16/18 GA, powder coated steel exterior; 16/18 GA type 304 SST work zone	16/18 GA, powder coated steel exterior; 16/18 GA type 304 SST work zone	16/18 GA, powder coated steel exterior; 16/18 GA type 304 SST work zone
Diffuser for Air Supply (Metal)	Non-flammable	Non-flammable	Non-flammable	Non-flammable
HEPA Filter Seal Type: Supply Filter-99.99% Eff. on 0.3 microns	HEPEX Seal- Neoprene, Spring-loaded	HEPEX Seal- Neoprene, Spring-loaded	HEPEX Seal- Neoprene, Spring-loaded	HEPEX Seal- Neoprene, Spring-loaded
Optional Services, (Total) Position:				
Service Coupling (3/8 inch NPT)	(3) Right/left sidewalls	(3) Right/left sidewalls	(3) Right/left sidewalls	(3) Right/left sidewalls
Gas Valve/Service Coupling (3/8inch NPT)	(3) Right/left sidewalls	(3) Right/left sidewalls	(3) Right/left sidewalls	(3) Right/left sidewalls
Outlet	(1) Right/left area under work surface	(1) Right/left area under work surface	(1) Right/left area under work surface	(1) Right/left area under work surface
Work Station Size Inches (mm):				
Height	55 3/8 (1406)	55 3/8 (1406)	55 3/8 (1406)	55 3/8 (1406)
Width	38 (965)	50 (1270)	62 (1575)	74 (1880)
Depth	32 (813)	32 (813)	32 (813)	32 (813)
Work Zone Inches (mm):				
Height	32 (813)	32 (813)	32 (813)	32 (813)
Width	35 7/8 (911)	47 7/8 (1216)	59 7/8 (1521)	71 7/8 (1826)
Depth	19 5/8 (498)	19 5/8 (498)	19 5/8 (498)	19 5/8 (498)
Airflow Volume at 90 fpm (.46 mps) CFM/CMH	718 (1220)	958 (1628)	1198 (2036)	1438 (2443)
Heat Rejected, BTU, Per Hour	863	1256	1648	1962
Electrical:	CE	CE	CE	CE
Volts, AC 50/60 Hz	230	230	230	230
+Amps: Blower/Lights (30"/36")	2.2	3.2	4.2	5.0
Rated Amps:	5	6	6	6
12 ft. Power Cord (one)	14 GA - 3 Wire, 15A	14 GA-3 Wire, 15A	14 GA-3 Wire, 15A	14 GA-3 Wire, 15A
Work Station Weights:***				
Crated Shipping Weight	330 lbs. /150 kg.	390 lbs. /177 kg.	450 lbs. /204 kg.	540 lbs. /245 kg.
Net Weight	290 lbs. /132 kg.	340 lbs. /154 kg.	400 lbs. /181 kg.	470 lbs. /213 kg.

***Crated shipping weight does not include weight for accessories or options

+ Based on Work station with new filters running at 230VAC.