

Table-top autoclaves Premium HMT 260 | 300 MB



Are you looking for a way to sterilize all heat resistant laboratory instruments? Then our HMT 260 | 300 MB is the perfect choice for you!

Features at first glance:

- > Certified according to regulation 93/42/EEC, B-series autoclave
- > Available in 2 sizes with a volume of 24 or 40 liters
- > Powerful integrated vacuum pump, an essential feature for sterilizing tubes and hollow components
- > Documentation / data storage via SD card and printer
- > Easy maintenance



Features:

- > Controlled by a microprocessor
- > Easy operation with a LCD display
- > Fractional pre-vacuum / drying vacuum
- > 4 liters water tank, to be filled manually or automatically (purified water)
- > Documentation / data storage via SD card and printer
- > Counter of cycles, calibration / service mode
- > Double water level monitoring (chamber / tank)
- > Mechanical-electrical chamber door lock
- > Many safety systems such as for example an overheating protection or a safety valve
- > Reset/emergency button

Autoclaving programs:

- > 5 sterilization programs: unwrapped 121 °C, 15 min.; unwrapped 134 °C, 4 min.; wrapped 121 °C, 30 min.; wrapped 134 °C, 15 min., Preset prion program (134 °C, 18 min.), additionally 1 individually adjustable program
- > 3 test programs: leakage test, helix test, Bowie-Dick test
- > Drying program, 1- 60 minutes
- > Additionally: Individual temperature selection from 105 to 135 °C

Table-top autoclaves HMT-Series	Unit	HMT 260 MB	НМТ 300 МВ				
ArtNr.		22014	22021				
Chamber volume	liters	24	40				
Chamber dimensions (Ø x D)	mm	260 x 450	300 x 570				
External dimensions (W x D x H)	mm	533 x 655 x 442	620 x 766 x 489				
Electrical power	kW	2.7	2.7				
Weight	kg	59	87				
Water tank	liters	4.2	2 x 4,2				
Power supply	V	AC 220 V / 240 V - 50/60 Hz					
Selectable operating temperature	° C	105 - 135	105 - 135				
Max. operating pressure	bar	2.1					
Sterilization time	min.	variable, 1 to 60 minutes	variable, 1 to 60 minutes				
Locking system		manual, electrically secured					
Certification		according to 93/42/EEC, CE 2460					
Vessel material		SUS304 (high-grade stainless steel)					
Vacuum		Yes	Yes				
Safety systems		Overheating protection, safety valve, overpressure switch, mechanical-electrical chamber door lock, water level monitoring of the reservoir and sterilization chamber					



From a batch system to loading baskets: our accessories make it possible to configurate the autoclave according to your requirements

HMT-Series / Loading capacities	Sterilizing box HMT 260 MB	Sterilizing box HMT 300 MB	Basket HMT 260 MB	Basket HMT 300 MB	Stacking system set HMT 260 MB	Stacking system set HMT 300 MB	Spiral holder (all devices)
Art-Nr.	52017	52039	52037	52038	52025	52054	52010
Ext. dimensions (W x D x H), mm	375 x 215 x 135	500 x 205 x 185	370 x 220 x 120	500 x 245 x 160	390 x 250 (max.) x 205 (max.)	550 x 290 (max.) x 245 (max.)	
Special characteristics	container with lid, side walls with closable holes		rectangular		set, consisting of a rack with plates or grid and removal aid		f. small items
Loading capacity per device	1	1	1	1	1	1	1

Sterilizing box



Art-Nr. 52017 | 52039: Container with lid, side walls with closable holes

Basket



Art-Nr. 52037 | 52038: Rectangular and optimally pervious to steam

Stacking system



Art-Nr. 52025 | 52054: Set, consisting of a rack with plates or grid and removal aid

Spiral holder



Art-Nr. 52010: For small items, 2 pieces

We also support
You in servicing your
HMC products. Just ask
for our maintenance
contracts!