



## 1-DOOR REFRIGERATED CABINET, HC ADVANCE K 70-4 L DR

Product Serie: Advance

Artikelnummer: 131701010

Hoshizaki ADVANCE is a series of durable refrigeration and freezer cabinets, exceeding the requirements of demanding commercial kitchen environments.

The Advance K 70-4 L DR is a 1-Door Refrigerated Cabinet, HC with a net internal volume of 415 liters. The outside dimensions are 654 x 830 x 1980-2030 mm.

### DURABLE MATERIALS

The interior and exterior are made of stainless steel, the best material for humid locations. ADVANCE cabinets are designed to withstand the demanding conditions of large kitchen operations.

### MAXIMUM STORAGE SPACE

With shelves all the way from the top to the bottom of the cabinet, the inside space can be efficiently utilized for maximum produce storage.

### HYGIENE AND FOOD SAFETY

Thanks to the rounded corners and seamless surfaces, frequented cleaning routines become a quick and simple task. The practical anti-tilting shelves prevent spillage. The cabinet has a rounded base and comes with removable gaskets for easy wiping.

### MONO-BLOCK DESIGN

The ADVANCE refrigeration system uses a mono-block construction. This brings two important advantages. As the evaporator is positioned on top of the cabinet, valuable space inside the cabinet can be used for storage. Additionally, it is removable for easier maintenance and repair.

### UNIFORM KITCHEN DESIGN

The exterior of all ADVANCE cabinets features a uniform design that fits seamlessly into your Hoshizaki kitchen concept.

### TEMPERATURE STABILITY

The intelligent air distribution system allows high performance, ensuring temperature stability despite frequent door openings and during defrosting.

## SPECIFICATIES

<b>Productnaam</b>	1-Door Refrigerated Cabinet, HC	<b>Energie verbruik Ecodesign (kWh/Jaar)</b>	548
<b>Temperatuurbereik</b>	0/+10°C	<b>Energie Efficiëntieklaasse (ISO 22041-2019)</b>	C
<b>Inhoud, bruto (liter)</b>	600	<b>Energie Efficiëntie Index EEI</b>	42.41
<b>Netto bruikbaar volume (liter)</b>	415	<b>Geluidsniveau – dB(A)</b>	50
<b>Uitwendig</b>	RvS	<b>Klimaatklasse</b>	5
<b>Inwendig</b>	RvS	<b>Poten / Wielset</b>	H = 130/180 mm (L)
<b>Afmetingen W x D x H (mm)</b>	654 x 830 x 1980-2030	<b>Koelmiddel (kg)</b>	0.058
<b>Gewicht, verpakt (kg)</b>	120	<b>CO2 Equivalent (kg)</b>	0.17
<b>Isolatie (mm)</b>	60 mm (polyurethaan)	<b>GN – Shelf size</b>	2/1 GN diep
<b>Koelmiddel</b>	R290	<b>Maximaal aantal roosters</b>	22
<b>GWP</b>	3	<b>Aantal roosters</b>	4
<b>Koelcapaciteit bij -10°C (Watt)</b>	361	<b>Uitgerust met</b>	Rechtsdraaiende omkeerbare deur met slot, automatische deursluiting, 4 grijze roosters, LED-verlichting
<b>Aansluiting</b>	230V, 50 Hz	<b>Deur type</b>	Geïsoleerde deur
<b>Aansluitwaarde (Watt)</b>	140		