
LR 270 W LITE







600

Color: White Panel: LITE

- LED backlit control panel
- Temperature display resolution 0,1°C
- Audible and visual alarms
- Dry contact for alarms signal remoting

TECHNICAL FEATURES		
Product Code	ABC700L	
Temperature	0°C / +15°C	
Refrigeration Type	Forced air	
Defrost Type	Automatic, with heating resistance	
Condensate Evaporation	Automatic	
Refrigerant Gas	R290	
Climatic Class	+16°C / +43°C (T)	
External Dimensions (W x D x H mm)	600 x 650 x 1620	

ELECTRICAL	$\mathbf{D}\mathbf{A}\mathbf{T}\mathbf{A}$

Power Supply (V/ph/Hz)

220-230/1/50

LR 270 W LITE



ELECTRICAL DATA

Power Plug Type F

STRUCTURAL FEATURES			
Structure	Upright		
External Material	Anti-bacterial coated steel white colour		
Internal Material	Stainless steel 18/10 AISI 304		
Insulation Thickness (mm)	50		
Insulated Door	Yes		
Door Reversibility	Yes		
Automatic Door Closure	Yes		
Shelves Number	2		
Shelf Material	Wire steel with white colour plastic coating		
Shelves Dimensions (W x D mm)	s Dimensions (W x D mm) 460 x 470		
Shelf Adjustment Step Range (mm)	100		
Maximum Shelf Quantity	-		
Drawers with extractable slides	Optional		
Drawer Adjustment Step Range (mm)	100		

CONTROL PANEL		
Display Type	LED	
Access Password	No	
Probe Type	Nr. 2 NTC	
Alarm Signaling	Acoustic and visual	
Alarm Indications	Codes	
Adjustable High/Low Temperature Alarm	Yes	
Adjustable Door Open Alarm	Yes	
Power Loss Alarm	Yes	

LR 270 W LITE



CONTROL PANEL		
Probe Fault Alarm	Yes	
Acoustic Alarm Silencing Options	Yes	
Calibration	Yes	
Alarm Memory	10	
Dry Contact	Yes (NC)	