
MPR 370 W LITE









Color: White Panel: LITE

- LED backlit control panel
- Temperature display resolution 0,1°C
- Audible and visual alarms
- Dry contact for alarms signal remoting

TECHNICAL FEATURES			
Product Code	AAD700L		
Temperature	+2°C / +15°C		
Refrigeration Type	Forced air		
Defrost Type	Automatic, with heating resistance		
Condensate Evaporation	Automatic		
Refrigerant Gas	R290		
Climatic Class	+16°C / +38°C (ST)		
External Dimensions (W x D x H mm)	600 x 670 x 2020		

MPR 370 W LITE



ELECTRICAL DATA		
Power Supply (V/ph/Hz)	220-230/1/50	
Power Plug	Type F	

	STRUCTURAL FEATURES	
Structure	Upright	
External Material	Anti-bacterial coated steel white colour	
Internal Material	Stainless steel 18/10 AISI 304	
Insulation Thickness (mm)	50	
Triple-Layer Glass Door	Yes	
Door Reversibility	Yes	
Automatic Door Closure	Yes	
Shelves Number	3	
Shelf Material	Wire steel with white colour plastic coating	
Shelves Dimensions (W x D mm)	460 x 470	
Maximum Shelf Quantity	-	

CONTROL PANEL		
Display Type	LED	
Access Password	No	
Probe Type	Nr. 2 NTC	
Alarm Signaling	Acoustic and visual	
Alarm Indications	Codes	
Adjustable High/Low Temperature Alarm	Yes	
Adjustable Door Open Alarm	Yes	
Power Loss Alarm	Yes	
Probe Fault Alarm	Yes	

MPR 370 W LITE



CONTROL PANEL		
Acoustic Alarm Silencing Options	Yes	
Calibration	Yes	
Alarm Memory	10	
Dry Contact	Yes (NC)	