
MPR 1365 W LITE









Color: White Panel: LITE

- LED backlit control panel
- Temperature display resolution 0,1°C
- Audible and visual alarms
- Dry contact for alarms signal remoting

TECHNICAL FEATURES		
Product Code	AAN650L	
Temperature	+2°C / +15°C	
Refrigeration Type	Forced air	
Defrost Type	Automatic, with heating resistance	
Condensate Evaporation	Automatic	
Refrigerant Gas	R290	
Climatic Class	+16°C / +38°C (ST)	
External Dimensions (W x D x H mm)	1500 x 870 x 2080	

ELECTRICAL DATA		
Power Supply (V/ph/Hz)	220-230/1/50	
Power Plug	Туре F	

MPR 1365 W LITE



STRUCTURAL FEATURES

Structure	Upright
External Material	Anti-bacterial coated steel white colour
Internal Material	Stainless steel 18/10 AISI 304
Insulation Thickness (mm)	75
Triple-Layer Glass Door	Yes
Automatic Door Closure	Yes
Shelves Number	6
Shelf Material	Wire steel with white colour plastic coating
Shelves Dimensions (W x D mm)	530 x 650
Shelf Adjustment Step Range (mm)	89
Maximum Shelf Quantity	-
Drawers with extractable slides	Optional
Drawer Adjustment Step Range (mm)	89

CONTROL PANEL		
Display Type	LED	
Access Password	No	
Probe Type	Nr. 2 NTC	
Alarm Signaling	Acoustic and visual	
Alarm Indications	Codes	
Adjustable High/Low Temperature Alarm	Yes	
Adjustable Door Open Alarm	Yes	
Power Loss Alarm	Yes	
Probe Fault Alarm	Yes	
Acoustic Alarm Silencing Options	Yes	
Calibration	Yes	
Alarm Memory	10	

MPR 1365 W LITE



Dry Contact	
-------------	--

CONTROL PANEL

Yes (NC)