





U

Color: White Panel: LITE

- LED backlit control panel
- Temperature display resolution 0,1°C
- Audible and visual alarms
- Dry contact for alarms signal remoting

TECHNICAL FEATURES		
Product Code	AGD700L	
Temperature	-25°C / -40°C	
Refrigeration Type	Forced air	
Defrost Type	Automatic, hot gas type	
Condensate Evaporation	Automatic	
Refrigerant Gas	HC	
Climatic Class	+16°C / +28°C	
External Dimensions (W x D x H mm)	600 x 660 x 1950	

ELECTRICAL DATA		
Power Supply (V/ph/Hz)	220-230/1/50	
Power Plug	Type F	

## PDF 370 W LITE



STRUCTURAL FEATURES				
Structure	Upright			
External Material	Anti-bacterial coated steel white colour			
Internal Material	Stainless steel 18/10 AISI 304			
Insulation Thickness (mm)	50			
Insulated Door	Yes			
Door Reversibility	Yes			
Automatic Door Closure	Yes			
Heated Door Seal	Yes			
Compensation Valve	Yes			
Shelves Number	3			
Shelf Material	Wire steel with white colour plastic coating			
Shelves Dimensions (W x D mm)	460 x 470			
Shelf Adjustment Step Range (mm)	100			
Maximum Shelf Quantity	-			
Drawers with extractable slides	Optional			
Drawer Adjustment Step Range (mm)	100			

CONTROL PANEL		
Display Type	LED	
Access Password	No	
Probe Type	Nr. 2 NTC	
Alarm Signaling	Acoustic and visual	
Alarm Indications	Codes	
Adjustable High/Low Temperature Alarm	Yes	
Adjustable Door Open Alarm	Yes	
Power Loss Alarm	Yes	
Probe Fault Alarm	Yes	

## PDF 370 W LITE



CONTROL PANEL		
Acoustic Alarm Silencing Options	Yes	
Calibration	Yes	
Alarm Memory	10	
Dry Contact	Yes (NC)	